

UTP Category 6 Cables

Content of Data Sheet				
Product model	CAB-LC3100			
Product specification	HSYV-6 4x2x0.57			
Test Standard	YD/T1019-2013			
Conductor	Material	Solid-Bare Copper		
	AWG	23		
	Nom.O.D.(mm)	0.57±0.005 mm		
	DC resistance	≤95 Ω/km		
Insulation	Material	HDPE		
	Thickness	0.2±0.02 mm		
	Diameter	1.02±0.05 mm		
Color	Blue/White- Blue	Green/White-Green	Electrical Characteristics: Frequency Characteristic impedance RL ATT NEXT	
	Orange /White-Orange	Brown/White-Brown		
Pitch	Offset pitch	≤20 mm		
	Cable pitch	≤120 mm		
Sheath	Material	PVC(complies RoHS/REAC)		
	External O.D.	6.2±0.3 mm		
	Color	Blue(RAL5015)		
	Tensile strength	>13.5 Mpa		
	Thickness	0.6±0.05 mm		
Surface Printing	Letter height	3.0±0.3 mm		
	Color	Black		
	Print error & Space	1±0.005 m		
	Case number	Yes		
	Packing	Packing	Carton	

	Once packing dimension			Frequency	FEXT	PS NEXT	PS FEXT	Phase delay
	420mm*205mm*420mm			MHz	≥dB/100m	≥dB/100m	≥dB/100m	≤ns/100m
	Twice packing dimension			1	63.8	72.3	64.8	570.0
	450mm*440mm*445mm			4	51.7	63.3	57.7	552.0
	Twice packing quantity			10	43.8	57.3	44.8	545.4
	2 cases			16	39.7	54.3	40.7	543.0
Packing length	305±1m			20	37.7	52.8	38.7	542.0
				31.25	33.9	49.9	34.9	540.4
Rip-cord	Yes	Crossing backbone	Yes	62.5	27.8	45.4	28.8	538.6
Ambient temperature	-20°C ~ 60°C			100	23.8	42.3	24.8	537.4
				150	20.2	39.4	20.9	536.0
				200	17.7	37.8	18.7	536.0
				250	15.8	36.3	16.8	536.0

Zhejiang Uniview Technologies Co.,Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2011-2017 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.